

## Claims

1. An installation for coating a workpiece with powder,  
wherein there is provided a powder spray device with  
5 a longitudinal axis and a principal spraying direction that differs from said longitudinal axis,  
wherein there is provided a carrier element,  
wherein said powder spray device is supported in such  
a manner as to capable of being rotated with respect  
10 to said carrier element, about a rotation axis and  
the principal spraying direction of the powder differs from said rotation axis.
2. An installation in accordance with claim 1,  
wherein said rotation axis runs parallel to said  
15 longitudinal axis of said powder spray device.
3. An installation in accordance with claim 1,  
wherein said powder spray device is provided with a  
nozzle and the alignment of said nozzle defines said  
principal spraying direction.
- 20 4. An installation in accordance with claim 1,  
wherein said powder spray device is designed as a  
spray pistol.
5. An installation in accordance with claim 1,  
wherein there is provided a booth and said powder  
25 spray device into said booth,  
wherein said carrier element is provided with a  
mounting and a guide arm, said powder spray device  
being connected with said guide arm by means of said  
mounting,  
30 and wherein said guide arm and said mounting are  
arranged outside said booth.

6. An installation in accordance with claim 5,  
wherein on the guide arm there is provided a first  
linear axle by means of which said powder spray device  
can be made to perform translatory movements along a  
first axis.  
5
7. An installation in accordance with claim 6,  
wherein said first linear axle is coupled with a sec-  
ond linear axle by means of which said powder spray  
device can be made to perform translatory movements  
along a second axis.  
10
8. An installation in accordance with claim 1,  
wherein said mounting is provided with a drive for  
the rotation of said powder spray device.
9. An installation in accordance with claim 8,  
wherein said drive is provided with a step motor.  
15
10. An installation in accordance with claim 1,  
with a further powder spray device.
11. An installation in accordance with claim 10,  
wherein said powder spray device and said further  
powder spray device are connected with said guide arm  
by means of said mounting and said first and/or said  
second linear axle.  
20
12. An installation in accordance with claim 10,  
wherein said further powder spray device is connected  
with said guide arm by means of a further mounting.  
25
13. An installation in accordance with claim 10,  
wherein said powder spray device is arranged on a  
first longitudinal side of said booth,  
wherein said further powder spray device is arranged  
on a second longitudinal side of said booth.  
30

14. An installation in accordance with claim 1,  
wherein there is provided a control unit for the rotation and the translations of said powder spray device.
- 5 15. An installation in accordance with claim,  
wherein there is provided a third linear axle by means of which said guide arm is arranged in a mobile manner on a third axis.